# ECHNICAL INFORMATION



Models No. ► LB1200F


Description ► Band Saw

## CONCEPT AND MAIN APPLICATIONS

Model LB1200F is 305mm Band Saw with high cutting efficiency.

Its main features and benefits are:

- 6 LED job light that illuminate working surface for easier cutting in dark places.
- Wheeled stand for easier mobility
- Quick-release tension lever for tool-less easy blade change
- High/low speed selection for excellent results in both hard and soft wood



Dimensions: mm (")				
Length (L)	615 (24-1/4)			
Width (W)	775 (30-1/2)			
Height (H)	1,600 (63)			

#### ► Specification

	Voltage (V)	Current (A)	Cycle (Hz)	Continuous Rating (W)		Moy Output (W)
				Input	Output	Max. Output (W)
	110 - 120	8.2	50/ 60	900	660	
	220 - 240	4.0	50/ 60	900	660	

Cutting speeds m/s (m/min)	50 Hz: Low/ High	6.7 (400)/ 13.3 (800)	
Cutting speed: m/s (m/min.)	60 Hz: Low/ High	8.3 (500)/ 16.7 (1,000)	
Plada sizar mm (")	Circumference	2,240 (88)	
Blade size: mm (")	Width	6 (1/4), 13 (1/2), 16 (5/8)	
Cutting conscitions mm (")	Maximum height	165 (6-1/2)	
Cutting capacities: mm (")	Throat width	305 (12)	
Mechanical speed control	•	Yes (2 speed)	
Protection against electric sho	ck	Grounding	
LED job light		Yes (6 LEDs)	
Power supply cord: m (ft)		2.5 (8.2)	
Weight according to EPTA-Procedure 01/2003*: kg (lbs)		81.2 (179.0)	

<sup>\*</sup> with stand and band saw blade

#### ► Standard equipment

Rip fence	Push stick2
Miter gauge	Nozzle 93 1
Saw blade for wood (6mm width) 1	Band saw stand 1
Saw blade for wood (13mm width) 1	Hex wrench 4 1
Saw blade for wood (16mm width) 1	Hex wrench 5 1
Saw blade for nonferrous metal (16mm width) 1	

**Note:** The standard equipment for the tool shown above may vary by country.

### Optional accessories

Extension table, Circular cutting attachment, Belt sanding attachment, Band saw blades, Dust collector port