




# TECHNICAL INFORMATION

**Model No.** ▶ BCF201

**Description** ▶ Cordless Fan



## CONCEPT AND MAIN APPLICATIONS

Model BCF201 is a Cordless Fan powered by 14.4V/18V Li-ion battery to provide air circulation or cooling for jobsite in all seasons.

Its main benefits are:

- Powered by both of 14.4V and 18V Li-ion batteries (3.0Ah: BL1430/ BL1430A , 1.3Ah: BL1415, 3.0Ah: BL1830, 1.3Ah: BL1815)
- Robust design suitable for jobsite use
- Elastomer bumpers to protect against rough handling in jobsite
- AC adapter (DC15V, 2500mA) available as a standard equipment.

This product is available in the following variations.

| Model No. | Battery |          | Charger | Housing color |
|-----------|---------|----------|---------|---------------|
|           | type    | quantity |         |               |
| BCF201Z   | No      | No       | No      | Makita-blue   |
| ---       |         |          |         |               |
| BCF201ZW  | No      | No       | No      | White         |
| ---       |         |          |         |               |

| Dimensions: mm (") |              |
|--------------------|--------------|
| Length (L)*3       | 263 (10-3/8) |
| Width (W)          | 330 (13)     |
| Height (H)         | 523 (20-5/8) |

\*3 119mm (4-11/16")  
when folded

All models also include the accessories listed below in "Standard equipment".

## ► Specification

| Specifications  |                                  | Model No. | BCF201  |                      |
|---|----------------------------------|-----------|---|----------------------|
| Battery   | Cell                             |           | Li-ion  |                      |
|   | Voltage: V                       |           | 14.4  | 18                   |
|   | Capacity: Ah                     |           | 3.0/ 1.3  | 3.0/ 1.3             |
|   | Energy capacity: Wh              |           | 44/ 19  | 54/ 24               |
|   | Charging time with DC18RC : min. |           | 22/ 15  | 22/ 15               |
| Continuous run time on a single full battery charge: (minute) | at High speed                    |           | 90/ 40  | 100/ 45              |
|   | at Low speed                     |           | 180/ 80   | 200/ 90              |
| Max. wind speed*2 (m/min)                                     |                                  |           | 120   |                      |
| Wind speed control  |                                  |           | Yes (2-speed)                                       |                      |
| Constant speed control  |                                  |           | Yes   |                      |
| Automatic-off timer   |                                  |           | Yes<br>3 stage adjustable: 1 hour, 2 hours, 4 hours |                      |
| Weight according to EPTA-Procedure 01/2003*3: kg (lbs)        |                                  |           | 2.6 (5.6)/ 2.4 (5.2)                                | 2.7 (5.9)/ 2.4 (5.4) |

\*2 measured at a point 1.0m away from the machine

\*3 with battery

## ► Standard equipment

AC adapter (DC15V, 2500mA) ..... 1

## ► Optional accessories

Battery: BL1415, BL1430, BL1430A, BL1815, BL1830

Charger: DC18RA (for USA, Canada, Guam, Panama, Mexico),  
DC18RC (except USA, Canada, Guam, Panama, Mexico),  
DC18SD, DC18SE (Automotive), DC24SC